

L150 Peristaltic Pump

www.enviroflexpumps.com | +44 (0) 1332 913 200 | sales@enviroflexpumps.com



PUMP SPECIFICATIONS

PUMP (HOSE) BORE

150mm (6")

MAX WORKING PRESSURE

10 BarG (145 PSI)

DISPLACEMENT PER REV

70 L/REV (18.492 US GAL/REV)

MAX CONTINUOUS SPEED

25 RPM

MAX INTERMITTENT SPEED

35 RPM

SOLIDS HANDLING


Soft: 120mm (4-3/4") Hard: 22.5mm (7/8")

MAX SUCTION LIFT (WATER)


9 Meters (27 Feet)

AVERAGE STANDARD WEIGHT

1800 KG (3960 LB)



L150 PERFORMANCE CURVE



*Optimal flow rates stated **Intermittent duty defined as 1 operation followed by a 20 minute rest


RUBBER HOSE MATERIALS

- ☐ Natural (NR)
- ☐ Food Grade Natural (FGNR)
- ☒ Nitrile Buna (NBR)
- ☒ Food Grade Nitrile Buna (FGNBR)
- ☒ Ethylene Propylene Diene Monomer (EDPM)
- ☒ Chlorosulfonated Polyethylene (CSM)
- ☒ Fluorine/Fluoro (FKM)

CONNECTION OPTIONS

- Victaulic (standard)
- Tri-Clamp*
- ANSI Class 150
- IDF
- Flanged
- RJT
- PN16 Flanged
- Camlock

GA DRAWING



**UK
CA**